

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 April 2004 (08.04.2004)

PCT

(10) International Publication Number
WO 2004/029416 A1

(51) International Patent Classification⁷:

F01D 5/18

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/GB2003/004094

(22) International Filing Date:

25 September 2003 (25.09.2003)

(25) Filing Language:

English

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(26) Publication Language:

English

(30) Priority Data:

0222352.7 26 September 2002 (26.09.2002) GB



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(71) Applicants and
(72) Inventors: DORLING, Kevin [GB/GB]; 25 Stanway Road, Shirley, Solihull B90 3JD (GB). MACDONALD, John [GB/GB]; 254 Rutland Road, West Bridford, Nottingham NG2 5EB (GB).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TURBINE BLADE TURBULATOR COOLING DESIGN



(57) **Abstract:** A turbine blade (10) includes internal channels (16) which provide a flow passage for a cooling medium to assist in cooling the blade (10) when in use, wherein the channels (16) include a plurality of turbulence promoting ribs (28, 60, 64, 70) mounted on the wall surfaces (44, 62, 66, 72) thereof. Each rib (28, 60, 64, 70) comprises two rib portions (30, 32) joined at one end to form a chevron junction (34), wherein the chevron junction (34) defines an angle (36) of between 80° and 120° and is directed into the flow of the cooling medium through the channels (16). Each rib portion (30, 32) of a rib (28, 60, 64, 70) defines a gap (40, 42) therein.

WO 2004/029416 A1